

SAFETY ROPE (To prevent tools from falling at heights)

Controlable in length and flexible coiled rope.

Applicable for any tool which has safety holes
Ex.ratchet wrenches and adjustable angle wrenches.

Falling loads up to 1kg of weight per tool.








Stainless wire core with direct catch hook PAT.P.

AR430DV • DR • DY • DB

Direct catch system slim hook can be connected with the tools.

Direct catch system can be hooked the thick tool which we could not hook before.

It use stainless wire core(SUS304) in poly-uretane cord(PPU), and revivality and duration is the best.



Diameter of cord / \$\phi 3.0mm
Diameter of stainless core / \$\phi 0.8mm

Item No.	Color	Weight(g)	Remarks
AR 430DV	Violet		
AR 430DR	Red	65	
AR 430DY	Yellow green	0.5	
AR 430DB	Clear Black		



Kevlar core

AR300KP

Flexbile,thin,and light type without feeling heavy work.

It use kevlar core of Dupont Inc. of the United States of America on the polyuretane cord.

✓ Normal length / 490mm
Maximum stretched length / 1,820mm
Diameter of soul / O.F.

Diameter of cord / 2.5mm
Diameter of kevlar core / 1.2mm

Color Weight(g) Remarks


•	Item No.	Color	Weight(g)	Remarks
	AR 300KP	Fluor scent purple	45	



Stainless wire core

AR350PP · PR · PY

It use stainless wire core in uretane code and duration is the best. Rope diameter is small and flexibile and revival of coil shap is speedy.



Diameter of cord / 3mm_Diameter of wire core / 1.0mm

Item No.	Color	Weight(g)	Remarks
AR 350PP	Fluor scent purple		
AR 350PR	Yellow	65	
AR 350PY	Pink		



Nylon rope core

AR230G • Y • P

It use nylon rope core in poly-uretane cord.

Working quality is very nice due to its flexibility.

→ Normal length / 520mm → → → → → → → → → → → → → → → → → →	
Maximum stretched length / 1,550mm	
	\supset
Diameter of cord / 5.5mm \(\square\)	

Diameter of cord / 5.5mm - Diameter of nylon core / 3.0mm

Item No.	Color	Weight(g)	Remarks
AR 230G	Green		
AR 230Y	Yellow	85	
AR 230P	Pink		

RATCHET HOLDER PAT.



RHD7

One way holder through the belt of woraking wear. New metal (vynil lazer)against anti-frinction.

Stable store of the tools due to slope finish of insertion and mid-bending type. With mesh pocket for a small thing. (Unit: mm)

Item No.	Full length	Width	Weight(g)	Remarks
RHD 7	264	5.8	8.5	

