



〈寸法表〉

単位 mm

型 No.	A	B	C	D	E	F	G1	G2	H	I	J	K	L	M	x	y	z	重量 kg
BSS3-3515	300	150.8	350	40	74.6	25	-	-	-	-	-	-	-	-	0.02	0.05	0.03	56
BSS3-4020	300	200.8	400	40	49.6	25	-	-	-	-	-	-	-	-	0.02	0.05	0.03	82
BSS4-3728	400	280.8	370	50	59.6	40	320	-	40	4	110	145	225	-	0.02	0.05	0.03	145
BSS4-5024	400	240.8	500	50	79.6	50	320	-	40	4	110	145	225	-	0.02	0.05	0.03	172
BSS4-5025	400	250.8	500	50	74.6	50	320	-	40	4	110	145	225	-	0.02	0.05	0.03	177
BSS4-5520	400	200.8	550	50	99.6	50	320	-	40	4	110	145	225	-	0.02	0.05	0.03	160
BSS4-5525	400	250.8	550	50	74.6	50	320	-	40	4	110	145	225	-	0.02	0.05	0.03	191
BSS4-6025	400	250.8	600	50	74.6	50	320	-	40	4	110	145	225	20	0.02	0.05	0.03	228
BSS5-4536	500	360.8	450	50	69.6	40	400	-	50	4	150	175	275	-	0.02	0.05	0.03	233
BSS5-5530	500	300.8	550	50	99.6	50	400	-	50	4	150	175	275	20	0.02	0.05	0.03	280
BSS5-6028	500	280.8	600	50	109.6	50	400	-	50	4	150	175	275	20	0.02	0.05	0.03	285
BSS5-6030	500	300.8	600	50	99.6	50	400	-	50	4	150	175	275	20	0.02	0.05	0.03	301
BSS5-7025	500	250.8	700	50	124.6	50	400	-	50	4	150	175	275	20	0.02	0.05	0.03	293
BSS6-5645	630	450.8	560	50	89.6	40	500	250	65	8	200	215	340	-	0.02	0.05	0.03	376
BSS6-6045	630	450.8	600	50	89.6	50	500	250	65	8	200	215	340	-	0.02	0.05	0.03	412
BSS6-7031	630	310.8	700	50	159.6	50	500	250	65	8	200	215	340	20	0.02	0.05	0.03	404
BSS6-7040	630	400.8	700	50	114.6	50	500	250	65	8	200	215	340	20	0.02	0.05	0.03	489
BSS6-7530	630	300.8	750	50	164.6	50	500	250	65	8	200	215	340	20	0.02	0.05	0.03	415
BSS6-7540	630	400.8	750	50	114.6	50	500	250	65	8	200	215	340	20	0.02	0.05	0.03	518
BSS8-7950	800	500.8	790	50	149.6	60	640	320	80	8	270	265	425	-	0.02	0.05	0.03	672
BSS8-8040	800	400.8	800	50	199.6	60	640	320	80	8	270	265	425	-	0.02	0.05	0.03	602
BSS8-8042	800	420.8	800	50	189.6	50	640	320	80	8	270	265	425	20	0.02	0.05	0.03	653
BSS8-8050	800	500.8	800	50	149.6	50	640	320	80	8	270	265	425	20	0.02	0.05	0.03	736
BSS8-9055	800	550.8	900	50	124.6	50	640	320	80	8	270	265	425	20	0.02	0.05	0.03	870

材 料 FC300  
MATERIAL  
株式会社 スーパーマール

品 名 MC用4面シクマフロック  
NAME スタンタートタイプ  
TEL 072-236-5937  
FAX 072-235-8990